

1. A construction layout stripping comprising:

- a. a pliable, non-elastic elongated base;
- b. repeating units disposed on the base, the repeating units having a plurality of pairs of uprights thereon on a single fixed spacing interval, each pair of uprights adapted

5 to define a partition for grippingly receiving a specified size of construction member, whereby, construction elements can be built of various sized construction members spaced apart at a single fixed interval without the need to measure and mark the spacing, and the members can be held in place while being fixedly attached to the construction element.

2. The construction layout stripping of claim 1 having on the base cutting ribs that provide a cutting means to allow a user to make a clean cut at a desired length with any type of cutting device.

3. The strip of claim 1 where the base is comprised of two layers; first, an elastic layer; and second, a non-elastic layer, the two layers being bonded together.

4. The construction layout stripping of claim 1, the base having a sticky surface for more securely grippingly engaging construction members placed into the partitions defined thereon.

5. The construction layout stripping of claim 1, the base having a sticky surface for grippingly engaging a surface to which it is being applied.

6. The construction layout stripping of claim 1 where the repeating units have partitions spaced apart so as to create the ability to space construction members on more than one spacing interval using the same stripping.

7. The construction layout stripping of claim 1, the repeating units having a set of partitions, each of which is adapted to receive a $1 \frac{5}{8}$ " framing member, the set comprising:

- a. a first partition;
- b. a second partition, having a center which is 16" from the center of the first partition;
- c. a third partition, having a center which is 8" from the center of the second partition;
- d. a fourth partition, having a center which is 8" from the center of the third partition;
- e. a sufficient length of base so that the center of the fourth partition is 16" from a center of the first partition of the next repeating unit,

whereby a user can place $1 \frac{5}{8}$ " framing members on either 16" or 24" centers.

8. The repeating units of claim 1 having a set of partitions, each of which is adapted to receive a 3 $\frac{5}{8}$ " framing member, the set comprising:

- a. a first partition;
- b. a second partition, having a center which is 16" from the center of the first partition;
- c. a third partition, having a center which is 8" from the center of the second partition;
- d. a fourth partition, having a center which is 8" from the center of the third partition;
- e. a sufficient length of base so that the center of the fourth partition is 16" from a center of the first partition of the next repeating unit,

whereby a user can place 3 $\frac{5}{8}$ " framing members on either 16" or 24" centers.

9. The repeating units of claim 1 having a set of partitions, each of which is adapted to receive a $\frac{1}{2}$ " framing member, the set comprising:

- a. a first partition;
- b. a second partition, having a center which is 16" from the center of the first partition;
- c. a third partition, having a center which is 8" from the center of the second partition;
- d. a fourth partition, having a center which is 8" from the center of the third partition;
- e. a sufficient length of base so that the center of the fourth partition is 16" from a center of the first partition of the next repeating unit,

whereby a user can place $\frac{1}{2}$ " framing members on either 16" or 24" centers.

10. The construction layout stripping of claim 1 having more than one set of partitions adapted to receive more than one size of construction member and to allow for more than one spacing interval for each size of member.

11. The construction layout stripping of claim 10 where partitions associated with each size of member and each spacing interval have a consistent identifier means for noting which interval and member they relate to which is different from the identifier means for other construction members and for different spacing intervals.

12. The strip of claim 1 having the following repeating units on the same construction layout stripping where adjoining partitions share a common upright, the strip comprising:

a. a set of partitions, each of which is adapted to receive a $1 \frac{5}{8}$ " framing member, the set including:

- i. a first partition,
- ii. a second partition, having a center which is 16" from the center of the first partition,
- iii. a third partition, having a center which is 8" from the center of the second partition,
- iv. a fourth partition, having a center which is 8" from the center of the third partition,
- v. a sufficient length of base so that the center of the fourth partition is 16" from a center of the first partition of the next repeating unit;

b. a set of partitions adjacent to the $1 \frac{5}{8}$ " partitions, each of which is adapted to receive a $3 \frac{5}{8}$ " framing member, the set including:

- i. first partition,
- ii. a second partition, having a center which is 16" from the center of the first partition,
- iii. a third partition, having a center which is 8" from the center of the second partition,
- iv. a fourth partition, having a center which is 8" from the center of the third partition,

- v. a sufficient length of base so that the center of the fourth partition is 16" from a center of the first partition of the next repeating unit;
- c. a set of partitions adjacent to the $1 \frac{5}{8}$ " partitions, each of which is adapted to receive a $\frac{1}{2}$ " framing member, the set including:
 - 5 i. a first partition,
 - ii. a second partition, having a center which is 16" from the center of the first partition,
 - iii. a third partition, having a center which is 8" from the center of the second partition,
 - 10 iv. a fourth partition, having a center which is 8" from the center of the third partition,
 - v. a sufficient length of base so that the center of the fourth partition is 16" from a center of the first partition of the next repeating unit,

whereby a user can place $1 \frac{5}{8}$ ", $3 \frac{5}{8}$ ", or $\frac{1}{2}$ " framing members on 16" or 24" centers using
15 the same construction layout stripping.

13. A method of assembling construction members comprising the steps of:

- a. providing the construction layout stripping of claim 1;
- b. placing more than one construction member into the partitions adapted to closely, grippingly receive the construction members at the desired fixed interval; and
- c. affixing the members in place at the desired interval.

5

14. The method of claim 12 where the construction layout stripping is provided on a roll.

1. A construction layout stripping comprising:

- a. a pliable, non-elastic elongated base;
- b. repeating units disposed on the base, the repeating units having a plurality of pairs of uprights thereon on ~~one~~ a single fixed spacing interval, each pair of uprights ~~defining~~ adapted to define a partition for grippingly receiving a specified size of ~~framing~~ construction member,

whereby, construction elements can be built of various sized construction members spaced apart at a single fixed ~~intervals~~ interval without the need to measure and mark, ~~in any weather condition~~, the spacing, and the members can be held in place while being fixedly attached to the construction element.

2. The construction layout stripping of claim 1 having on the base cutting ribs that provide an easy cutting means to allow a user to make a clean cut at a desired length with any type of cutting device.

3. The strip of claim 1 where the base is comprised of two layers; first, an elastic layer; and second, a non-elastic layer, the two layers being bonded together.

4. The construction layout stripping of claim 1, the base having a sticky surface for more securely grippingly engaging ~~framing~~construction members placed into the partitions defined thereon.

5. The construction layout stripping of claim 1, the base having a sticky surface for grippingly engaging ~~the~~^a surface to which it is being applied.

6. The construction layout stripping of claim 1 where the repeating units have partitions spaced apart so as to create the ability to space construction members on more than one spacing interval using the same stripping.

7. The construction layout stripping of claim 1, the repeating units having a set of partitions, each of which is adapted to receive a $1\frac{5}{8}$ " framing member, the set comprising:

- a. a first partition;
- b. a second partition, having a center which is 16" from the center of the first partition;
- c. a third partition, having a center which is 8" from the center of the second partition;
- d. a fourth partition, having a center which is 8" from the center of the third partition;
- e. a sufficient length of base so that the center of the fourth partition is 16" from a center of the first partition of the next repeating unit,

whereby a user can place $1\frac{5}{8}$ " framing members on either 16" or 24" centers.

8. The repeating units of claim 1 having a set of partitions, each of which is adapted to receive a $3\frac{5}{8}$ " framing member, the set comprising:

- a. a first partition;
- b. a second partition, having a center which is 16" from the center of the first partition;
- c. a third partition, having a center which is 8" from the center of the second partition;
- d. a fourth partition, having a center which is 8" from the center of the third partition;
- e. a sufficient length of base so that the center of the fourth partition is 16" from a center of the first partition of the next repeating unit,

whereby a user can place $3\frac{5}{8}$ " framing members on either 16" or 24" centers.

9. The repeating units of claim 1 having a set of partitions, each of which is adapted to receive a $\frac{1}{2}$ " framing member, the set comprising:

- a. a first partition;
- b. a second partition, having a center which is 16" from the center of the first partition;
- c. a third partition, having a center which is 8" from the center of the second partition;
- d. a fourth partition, having a center which is 8" from the center of the third partition;
- e. a sufficient length of base so that the center of the fourth partition is 16" from a center of the first partition of the next repeating unit,

whereby a user can place $\frac{1}{2}$ " framing members on either 16" or 24" centers.

10. The construction layout stripping of claim 1 having more than one set of partitions adapted to receive more than one size of construction member and to allow for more than one spacing interval for each size of member.

11. The construction layout stripping of claim 10 where partitions associated with each size of member and each spacing interval have a consistent color, number, or letter identifier means for noting which interval and member they relate to which is different from the color, number, or letter of partitions identifier means for other framing construction members and for different spacing intervals.

5

12. The strip of claim 1 having the following repeating units of claims 7, 8, and 9 adjacent to each other on the same construction layout stripping where adjoining partitions share a common upright, the strip comprising:

a. a set of partitions, each of which is adapted to receive a $1\frac{5}{8}$ " framing member,

the set including:

i. a first partition,

ii. a second partition, having a center which is 16" from the center of the first partition,

iii. a third partition, having a center which is 8" from the center of the second partition,

iv. a fourth partition, having a center which is 8" from the center of the third partition,

v. a sufficient length of base so that the center of the fourth partition is 16" from a center of the first partition of the next repeating unit;

b. a set of partitions adjacent to the $1\frac{5}{8}$ " partitions, each of which is adapted to receive a $3\frac{5}{8}$ " framing member, the set including:

i. first partition,

ii. a second partition, having a center which is 16" from the center of the first partition,

iii. a third partition, having a center which is 8" from the center of the second partition,

iv. a fourth partition, having a center which is 8" from the center of the

third partition,

v. a sufficient length of base so that the center of the fourth partition is 16"
from a center of the first partition of the next repeating unit;

5 c. a set of partitions adjacent to the $1\frac{5}{8}$ " partitions, each of which is adapted to
receive a $\frac{1}{2}$ " framing member, the set including:

i. a first partition,

ii. a second partition, having a center which is 16" from the center of the
first partition,

10 iii. a third partition, having a center which is 8" from the center of the
second partition,

iv. a fourth partition, having a center which is 8" from the center of the
third partition,

v. a sufficient length of base so that the center of the fourth partition is 16"
15 from a center of the first partition of the next repeating unit,

whereby a user can place $1\frac{5}{8}$ ", $3\frac{5}{8}$ ", or $\frac{1}{2}$ " framing members on 16" or 24" centers using
the same construction layout stripping.

13. A method of assembling construction members comprising the steps of:

- a. providing the construction layout stripping of claim 1;
- b. placing more than one framing construction member into the ~~appropriate~~ partitions adapted to closely, grippingly receive the framing construction members at the desired fixed interval; and
- c. affixing the members in place at the desired interval.

5

14. The method of claim 12 where the construction layout stripping is provided on a roll.

UTILITY PATENT APPLICATION

COVER SHEET

Inventor(s): Richard M. Wichester
16579 Clayton Road
Wildwood, MO 63011

Attorney: Edward L. White
Reg. No. 41,375

Corresp. Edward L. White, P.C.
Address: 50 Penn Place, 4th Floor
1900 N.W. Expressway
Oklahoma City, OK 73118-1803
Phone: 405/810-8188
Facsimile: 405/842-0336

Title: **Construction Layout Stripping Having Gripping Uprights Thereon**

TITLE OF THE INVENTION

Construction Layout Stripping Having Gripping Uprights Thereon

CROSS REFERENCES TO RELATED APPLICATIONS

This application is a continuation-in-part of U.S. Patent Application No. 09/356,300 for
5 Construction Layout Stripping, filed 07/16/99.

BACKGROUND OF THE INVENTION

a. Field of the Invention

The invention relates to devices intended to ease and speed construction. In particular, the present invention is related to providing a means for laying out construction members or framing
10 members at a fixed distance interval one from another.

b. Description of the Prior Art

In the construction industry it is necessary to place multiple construction members or framing members at a fixed interval one from another in order to create a construction element such as a wall, a roof, a sub-floor, or a truss. Traditionally, tape measures have been used to set the distances, then
15 mark the placement of the construction member. Use of a tape measurer and a marker is time consuming and subject to mistakes. In addition, even after the construction members are placed on the mark, it can be moved or jarred easily so that it must be reset to the proper position. Great difficulty is encountered by the installer attempting to hold multiple construction members in place in preparation for permanently affixing them in position.

20 It is known in the prior art to provide devices for equally spacing construction members. For example, U.S. Pat. No. 5,797,233 to Hascall discloses a pre-spaced time-saving track for mounting studs for the construction of drywall or other wall surfaces. Hascall's device is intended to be used

with metal studs having a c-shaped construction. The track is constructed of metal, as is a rigid c-shaped member. As specified intervals it has a pair of tabs adapted to receive the c-shaped metal studs. However, Hascall's device was not designed to work with wooden studs. In addition, it is relatively expensive. It is only capable of receiving one size of stud member. For a different sized member, a different sized track would be required. Thus, Hascall's device is only useful for metal studs for framing wall members. Other construction elements such as roofs, sub-floors, trusses, and other such elements could not be used with this particular device.

SUMMARY OF THE INVENTION

In view of the foregoing disadvantages inherent in the known types of the present invention relates to devices, it is an object of the invention to provide an apparatus which overcomes the various disadvantages of the prior art.

It is therefore an object of the present invention to provide construction layout stripping for use in fabricating and installation of construction elements. It is a further object of the present invention to provide construction layout stripping which can be used with a plurality of framing members of varying widths and thicknesses. It is also an object of the present invention to provide construction layout stripping which could be used with metal, wood, or other construction materials.

It is a further object of the present invention to provide construction layout stripping having thereon the capability of receiving multiple sizes of construction members, and for spacing those construction members at more than one spacing interval. In an embodiment for use in wood construction, the construction layout stripping defines a set of partitions, each of which are adapted to receive 1 5/8", 3 5/8", or 1/2" construction members, and is adapted to space said members at either 16" or 24" center to center. Also, the present invention can be used with other standard spacings

currently used in the construction industry or which may hereafter be developed to accommodate new materials of construction or different needs. Construction layout stripping can be scaled to all universally accepted units of measurement including, but not limited to, united standard inches and metric scaling.

5 It is also an object of the present invention to provide construction layout stripping having an easy means for performing a straight cut at the desired length. To this end, it is an object of the present invention to provide construction layout stripping having cutting ribs thereon at small intervals spaced along the length of the stripping for guiding a cutting device in a straight line. Further, the construction layout stripping may have projections at the edge of the base defining
10 grooves to further ease cutting the construction layout stripping.

 It is a further object of the present invention to provide construction layout stripping which can be marketed in any individual lengths or on a roll for easy use by rolling out the construction layout stripping as needed at the construction site. The construction layout stripping is then fastened in place and ready to receive construction elements. The construction layout stripping may be held
15 in place by nails, screws, staples, glue, a self-adhesive backing or other like means. It is a further object of the present invention to provide temporary stability while affixing framing members into contact therewith.

 It is also an optional object of the present invention to provide construction layout stripping having color, number, or letter coded sections corresponding the different sized frame members to
20 be received and different spacing intervals on which whose members are to be spaced.

 It is an object of the present invention to provide a method for assembling construction elements comprising the steps of providing construction layout stripping according to the present

invention, placing a plurality of framing members into the partitions adapted to receive them at the desired fixed intervals, in preparation for the fixing of members in place at the desired interval. The layout of construction projects, commercial and residential, in the past took considerable time by the project's lead carpenter, and most times an additional assistant. Construction layout stripping
5 requires only one person who does not have to be a lead carpenter or even be trained in carpentry layout procedures. With construction layout stripping, one man can perform the same task - mistake proof - in one-half the time. The actual installation time required of all framing members is also greatly reduced due to the fact the construction layout stripping's uprights hold all members in place while nailing.

10 It is also an object of the invention to eliminate the need for measurement and marking of locations for construction members. Construction layout stripping allows work in all kinds of weather under which construction typically takes place. Whereas previously rain, ice or other inclement weather could obscure pencil marks, construction layout stripping is not affected by the weather due to the fact that construction layout stripping will be manufactured out of water resistant
15 materials. Adverse factors common to construction sites such as cold, heat, rain, snow, ice, dirt, sawdust, etc., will not result in construction delays as in the past with lead pencil layout markings.

Finally, it is an object of the present invention to provide construction layout stripping which can be used in the manufacturing industry. For example, where manufactured items require spacing similar elements at regular fixed intervals, construction layout stripping could easily be adapted to
20 the needs of a manufacturing process.

There has thus been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof that follows may be better understood, and in order that

the present contribution to the art may be better appreciated. There are, of course, additional features of the invention that will be described hereinafter and which will form the subject matter of the claims appended hereto.

In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in this application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting. As such, those skilled in the art will appreciate that the conception, upon which this disclosure is based, may readily be utilized as a basis for the designing of other structures, methods and systems for carrying out the several purposes of the present invention. Additional benefits and advantages of the present invention will become apparent in those skilled in the art to which the present invention relates from the subsequent description of the preferred embodiment and the appended claims, taken in conjunction with the accompanying drawings. It is important, therefore, that the claims be regarded as including such equivalent constructions insofar as they do not depart from the spirit and scope of the present invention.

Further, the purpose of the foregoing abstract is to enable the U.S. Patent and Trademark Office and the public generally, and especially the scientist, engineers and practitioners in the art who are not familiar with patent or legal terms or phraseology, to determine quickly from a cursory inspection the nature and essence of the technical disclosure of the application. The abstract is neither intended to define the invention of the application which is measured by the claims, nor is

it intended to be limiting as to the scope of the invention in any way.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be better understood and the objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such
5 description makes reference to the annexed drawings wherein:

FIG. 1 is a perspective view of one embodiment of the present invention.

FIG. 2 is detailed view of the construction layout stripping showing the cutting ribs and the
uprights.

FIG. 3 is a cross sectional side view showing the cutting ribs.

10 FIG. 4 is a cross sectional side view showing the cutting ribs and a two layer version of the construction layout stripping having an elastic layer and a non-elastic layer.

FIG. 5 is a cross sectional side view of the construction layout stripping being dispensed
from a roll.

FIG. 6 is a front view of the construction layout stripping on the roll.

15 FIG. 7 is a schematic view of the present invention used in a typical structure with multiple types of construction elements.

FIG. 8 is a top view of mating male and female end-pieces.

FIG. 9 is a detailed top view of the edge of the base.

FIG. 10 is a detailed side view of the edge of the base.

20 FIG. 11 is a partial cross-section perspective view of a dispenser for the construction layout stripping.

FIG. 12 is a top view of various sizes of framing members received in the construction layout

stripping.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Referring now to the drawings, where like numerals represent like parts, the construction layout stripping **10** is generally shown in FIG. 1. It has a base **12** which is comprised of a pliable, non-elastic elongated material. The material will be as non-elastic as possible so stretching or contracting of the fixed spacing on the partitions will be insignificant. The base **12** may be constructed from fabrics of various sorts, such as cotton, nylon, rayon, silk, and the like. However, the base **12** will preferably be composed of rubber, plastic, polyvinyl chloride, polyethylene, high density polyethylene, rayon, natural rubber, or other similar materials. Where rubber or plastic materials are used, it must be kept in mind that the strip must be non-elastic. Whatever materials are chosen, they must have a relatively low coefficient of thermal expansion/contraction. That is, a material which expands or contracts significantly in response to changes in temperature is not a suitable material of construction for the present invention. Excessive expansion/contraction would alter the predetermined spacing on the construction layout stripping. The base **12** may be comprised of a single layer as shown in FIG. 3. Alternatively, the base **12** may be comprised of two layers, an elastic layer **52** and a non-elastic layer **54**. For example, where it is desired to use an elastic material such as natural rubber for the base **12**, a material having elasticity, a second, non-elastic layer **54**, would be bonded thereto to prevent the distances between the various partitions from varying. It may be desirable to use a material having elasticity, such as rubber, because if such a material is used, an upright **16** for defining partitions **18** through **40**, can be molded in the same step during which the base **12** is formed. It is even possible that the base **12** could be made out of a metallic material. Aluminum, tin, or some other metal or alloy thereof could be used, so long as it is pliable

and non-elastic. Different materials of construction will be preferred for different applications. Materials of construction are not the critical issue involved in the present invention. The base 12 must simply be composed of a pliable, substantially non-elastic material.

FIG. 2 highlights cutting ribs 14 disposed along the base 12. The cutting ribs 14 provide an easy means to allow a user to make a clean cut at a desired length. A user simply runs a cutting device, such as a utility knife or a pair of snips or scissors, along the cutting rib 14 at the desired length.—

FIG. 1 shows an embodiment of the present invention having repetitive units 42 with a plurality of pairs of uprights 16 on at least one predetermined fixed interval, each pair of uprights 16 is spaced for receiving a specified size of framing member. This allows construction elements to be built out of framing members spaced apart at fixed intervals without the need to measure the spacing. The members can be held in place by their placement between a pair of uprights prior to fixedly attaching the construction elements. In FIG. 1, the repetitive unit 42 is composed of the following partitions: a first $1\frac{5}{8}$ " partition 18; a second $1\frac{5}{8}$ " partition 20, having its center 16" from the first partition 18; a third $1\frac{5}{8}$ " partition 22, having its center 8" from the center of the second partition 20; a fourth $1\frac{5}{8}$ " partition 24, having its center 8" from the third partition 22; a first $3\frac{5}{8}$ " partition 26 directly adjoining the first $1\frac{5}{8}$ " partition 18, and sharing a common upright 16 therewith; a second $3\frac{5}{8}$ " partition 28, having its center 16" from the first $3\frac{5}{8}$ " partition 26; a third $3\frac{5}{8}$ " partition 30, having its center 8" from the second partition 28; a fourth $3\frac{5}{8}$ " partition 32, having its center 8" from the third partition 30; a first $\frac{1}{2}$ " partition 34, directly adjacent to and sharing an upright 16 with the first $3\frac{5}{8}$ " partition 26; a second $\frac{1}{2}$ " partition 36, having its center 16" from the first partition 34; a third $\frac{1}{2}$ " partition 38, having its center 8" from the second partition 36;

and finally, a fourth $\frac{1}{2}$ " partition 40, having its center 8" from the third partition 38. The repetitive unit 42 further includes sufficient length of base to extend to the beginning of the next first $1\frac{5}{8}$ " partition 18 of the next repetitive unit. Similarly, the first $3\frac{5}{8}$ " partition 26 shares a side wall with the first $\frac{1}{2}$ " partition 34.—

5 The layout shown in FIG. 1 is only one example of the types of construction members and the distances with which the present invention can be used. In steel construction, it is common to use greater spacing than in wood construction. In addition, steel members come in a wide variety of shapes and sizes. Therefore, the nature of the construction stripping for use with steel members might be dramatically different than that shown in FIG. 1. However, FIG. 1 is shown for illustrating
10 the purposes as a typical configuration for wood construction. Similarly, a variety of spacings and construction members would be used if the present invention were to be adapted for use in manufacturing. A similar concept would be used for steel construction, though the partitions might have a different appearance.

 The construction layout stripping 10 of the present invention may be sold on a roll 56 as
15 shown in FIGs. 5 and 6. The roll 56 has sidewalls 58 and a center 60. The construction layout stripping 10 is wound thereon to be unrolled as needed. Alternatively, the construction layout stripping 10 could be sold in individual boxed lengths. If sold in boxed lengths, the construction layout stripping would preferably be cut into sections having whole numbers of repetitive units 42 thereon. Further, the ends of the lengths would preferably have both a male end 64 and a female end
20 66 to ease piecing them together into longer lengths.

 FIG. 7 shows the construction layout stripping 10 in use on a typical structure. The construction layout stripping 10 is shown in use on roof framing members 46, sub-floor framing

members 48, and wall framing members 50.

The construction layout stripping 10 may be coated with a sticky substance so that it more
effectively grippingly engages framing members placed into contact therewith and/or the surface to
which it is being applied. The construction layout stripping 10 may also have the uprights 16 color,
5 number, or letter coded so that the partition associated with each size of framing member and with
each spacing interval has the same color as other like numbers. For example, in FIG. 1 the uprights
16 or base 12 associated with the second 1 5/8" partition 20 and the fourth 1 5/8" partition 24, both of
which are associated only with 16" spacing, could have the same color, for example green. The third
1 5/8" partition 22, which is associated only with 24" spacing, could have a different color, for
10 example yellow. The first 1 5/8" partition 18, which is associated both with the 16" and the 24"
spacing would have yet a different color, for example red. The same pattern would hold true for the
set of 3 5/8" partitions, 26 through 32, and for the set of 1/2" partitions, 34 through 40.

FIG. 8 illustrates a variation in a terminal point of the construction layout stripping. A male
end 64 and a female end 66 are shown. The male end 64 and the female end 66 are adapted to be
15 matingly received, one within the other, so that if the construction layout stripping is provided in
fixed lengths, the units can be accurately adapted to be received within one another to maintain the
appropriate spacing. The male end 64 and the female end 66 may be adapted to snap together, be
welded together by glue or other suitable processes, or to be simply laid side by side then fastened
in place with nails, screws, staples, or other fasteners.

20 FIGS. 9 and 10 illustrate one variation on the edge of the base 12. An edge groove 68 is
defined by projections 70. Preferably, the edge groove 68 is spaced so as to correspond with the
cutting ribs 14.

FIG. 11 shows a box 72 adapted to receive the construction layout stripping 10. The box is comprised of side walls 58b, a center 60, which is essentially a tube adapted to receive the construction layout stripping 10 and enclosed sides 76 defining an opening 74 there through, through which the construction layout stripping 10 can pass. It is believed that a box 72 having the dimensions of 14" x 14" x 4" wide would be appropriately sized to receive approximately 100' of construction layout stripping 10 if the center 60b is approximately 4" in diameter. Preferably, the construction layout stripping will be attached to a cylinder which rotates about a shaft, which is the center 60b. This allows the construction layout stripping 10 to be more easily dispensed.

FIG. 12 shows several framing members placed on the construction layout stripping 10. As shown, the members are laying length-wise on the stripping. However, it should be understood that the framing members could also be standing upright. Also, note that each piece of construction layout stripping 10 will ordinarily receive only one type of construction member in the field, rather than the three different sizes shown in FIG. 12.

OPERATION OF APPARATUS

In operation, a user lays out the needed amount of construction layout stripping, affixes it in place with sticky tape, staples, nails, screws, etc., then places the desired members along the desired spacing thereon. The user can then permanently fasten the members into place as needed. Pairs of uprights 16 hold the members in the partitions 18 through 40 until they are fastened. This eliminates the need to re-adjust the spacing of the members and eliminates human mis-measuring mistakes.

Having thus described the field of the invention, the prior art, the attached drawings, the summary of the invention, and the detailed description of the preferred embodiments, I claim:

ABSTRACT

The present invention relates to devices intended to ease An improved apparatus and speed method for laying out construction members or framing members at a fixed distance interval from one another. In particular, the present invention is related to providing a means for laying out The construction members or framing members layout stripping comprises: first, a pliable, non-elastic elongated base; and second, repeating units disposed on the base, the repeating units distance interval from one another having a plurality of pairs of uprights thereon at fixed intervals, each pair of uprights defining a partition for receiving a specified size of framing member. The construction layout stripping of the present invention comprises: first, a pliable, non-elastic elongated base; and second, repeating units disposed on the base, the repeating units having a plurality allows construction elements to be built of pairs of a defining upright thereon various sized construction members spaced apart at fixed intervals, each pair of uprights defining a partition for receiving a specified size of framing member without the need to measure and mark the spacing, and also holds those members in place while they are fixedly attached to the construction element. The construction layout stripping of the present invention allows construction elements to be built of various sized construction members spaced apart at fixed intervals without the need to measure and mark the spacing, and the present invention also holds those members in place while they are fixedly attached to the construction element. In a preferred embodiment, the construction layout stripping has uprights defining spaces for receiving, but not limited to, 1 $\frac{5}{8}$ ", 3 $\frac{5}{8}$ ", and $\frac{1}{2}$ " framing members on, but not limited to, either 16" or 24" centers using the same construction layout stripping. The construction layout stripping has may have cutting ribs defined thereon which make cutting off a desired length of the construction layout stripping

easier by defining channels through which a utility knife is passed to cleanly cut off the ~~construction~~ layout-stripping. ~~The present invention~~It may be provided with any desired unit of spacing, or partitioned using any system of measurement (e.g., metric or U.S.) for any size of construction element.